

# Tiandy



TC-C34UP Spec:W/E/Y/M/4mm/V4.0

## 4MP Fixed Color Maker Bullet Camera

Lite Series



### KEY FEATURES

- Metal Housing
- Up to 2592x1520@25fps
- S+265/H.265/H.264
- Min. illumination Color: 0.0004Lux@F1.0
- 120dB WDR
- 4 Warmlights, 15m
- Support tripwire and perimeter
- Built-in Mic, support max 512G Micro SD Card
- Operating Conditions -40°C~65°C, 0~95% RH
- POE,DC12V
- IP67



**Tiandy Technologies Co.,Ltd.**

Email: [sales@tiandy.com](mailto:sales@tiandy.com)

Tel: +86-22-58596065

Website: [en.tiandy.com](http://en.tiandy.com)

Fax: +86-22-58596048



## SPECIFICATIONS

<b>Camera</b>	
Image Sensor	1/1.8"CMOS
Min. Illumination	Color:0.0004Lux@(F1.0,AGC ON)
Shutter Time	1s-1/100000s
Day&Night	N/A
WDR	120dB
S/N	>43dB
Angle Adjustment	0-360°;0-90°;0-360°
<b>Lens</b>	
Lens Type	Fixed
Focal Length	4mm
Lens Mount	M16
Aperture Range	F1.0,Fixed
Field of View	92.1°(H);49°(V);104.3°(D)
DORI Distance	Detect:53.3m Observe:21.1m Recognize:10.6m Identify:5.3m
<b>Illuminator</b>	
IR LEDs	N/A
IR Distance	N/A
Wavelength	N/A
White LEDs	4
Whitelight Distance	15m
<b>Compression Standard</b>	
Video Compression	S+265/H.265/H.264B/H.264M/H.264H
Video Bit Rate	32k-6Mbps
Audio Compression	G.711A/G.711U/ADPCM_D
Audio Sampling Rate	8kHz/32kHz/48kHz


# Tiandy

Image	
Max. Resolution	2592x1520@25fps
Main Stream	PAL:25fps(2592x1520,2560x1440,2304x1296,1920x1080,1280x720) NTSC:24fps(2592x1520,2560x1440),30fps(2304x1296,1920x1080,1280x720)
Sub Stream	PAL:25fps(704x576,704x288,640x360,352x288) NTSC:30fps(704x480,704x240,640x360,352x240)
Third Stream	N/A
BLC	Yes
HLC	Yes
AGC	Yes
3D DNR	Yes
White Balance	Auto/Semi-auto/Manual/Sunny/Natural light/Warm light/Sodium lamp/Incandescent lamp/Locked white balance
ROI	8 regions
Corridor mode	N/A
EIS	N/A
OSD	1region;16*16/32*32/48*48/64*64
Picture Overlay	N/A
Privacy Mask	4 regions
Defog	Yes
Feature	
Alarm Trigger	Motion Detection;Mask Alarm;Disk Full;Disk R/W Error;IP Address Conflict
Linkage Method	trigger recording;trigger capture;notify surveillance center
Video Analytics	Tripwire;Perimeter

# Tiandy

Rules of behavior analyse in 1 scene	2
Early Warning(EW)	N/A
Auto-Tracking	N/A
Face Mode	N/A
Face Detection Performance	N/A
<b>Network</b>	
ANR	ANR
Protocols	HTTP;HTTPS;TCP/IP;UDP;UPnP;ICMP;DHCP;DNS;DDNS;Easy DDNS;NTP;QoS;IPv4;SSH;Unicast;RTSP;FTP
System Compatibility	P2P(Mutually exclusive with Profile G);onvif Profile S/T/G;CGI;MIL STONE
Remote Connection	≤2
Client	Easy7 Smart Client
Moblie Client	EasyLive Plus
Web	IE10+;Firefox52+;Edge89+;Safari11+;Chrome57+
<b>Interface</b>	
Communication Interface	1 RJ45 10M/ 100M self adaptive Ethernet port
Audio I/O	N/A
Alarm I/O	N/A
Built-In Mic	Yes
Built-In Speaker	N/A
Reset Button	Yes
On-board storage	Built-in Micro SD card slot, up to 512 GB
Additional interfaces	N/A
<b>General</b>	
Web Client Language	19languages Simple Chinese/Traditional Chinese/English/Spanish/Korean/Italian/Turkish/Russian/Thai/French/Polish/Dutch/Hebrew/Arabic/Vietnamese/German/Ukrainian/Portuguese/Albanian
Operating Temperature	-40°C-65°C
Operating Humidity	0-95%
Storage Temperature	-40°C-65°C
Storage Humidity	0-95%(non-condensing)
Power Supply	DC12V±25%,MAX 8W;POE 802.3af,MAX 9W
Protection	Surge protection 2000V;Lightning proof 6000V;IP67
Boundary Dimensions	239(L)90(W)90(H)mm
Package Dimensions	280(L)125(W)140(H)mm
GrossWeight	1.28kg
NetWeight	0.92kg

## DIMENSIONS (Unit: mm)



## ACCESSORIES



A36



TC-P54BM SpecV5